

PCIe x16 Gen 3 Host to Target Kit (3811)

Part Number: OSS-KIT-EXP-3811



FEATURES

- Operates at 128Gb/s
- PCIe x16 switch-based host cable adapter can be inserted into a x16 slot of a host enclosure
- PCIe x16 cable with x16 connectors in 1M, 2M and 3M lengths
- Works with any OSS expansion backplane
- (Backplane sold separately)

The PCIe x16 Gen 3 expansion kit connects a server to one I/O card. The PCIe x16 Gen 3 switch-based cable adapter plugs into a server and cables to a PCIe x16 Gen 3 switch-based target cable adapter.

SPECIFICATIONS

PCIe x16 Cable Adapter

Form Factor	PCIe half card
Operating Temperature	0 °C to +70 °C environment
Storage Temperature	-40 °C to 85 °C
Operating Humidity	10% to 90% relative humidity non-condensing
Storage Humidity	5% to 95% relative humidity non-condensing
Power	1.5A @ 3.3V; 900mA @ 12V; 250mA @ 3.3V (aux)
Connectors	<ul style="list-style-type: none"> PCIe x16 cable connector PCIe x16 edge connector
Industry Specifications	<ul style="list-style-type: none"> PCIe External Cabling Specification, Rev. 1.0 PCI Express™ Card Electromechanical Specification, Rev. 3.0 PCI Express® Base Specification, Rev. 3.0 ATX Specification, Version 2.2
PCB	PCI Express add-in card standard PCIe x16 cable PCB thickness .063 +/-0.008 inch (1.6 +/- 0.2mm) Mounting holes for face plate
Switch	PLX 8732
Bracket	<ul style="list-style-type: none"> Standard and low profile brackets available Two LEDs on bracket
Agency Compliance (designed to meet)	<ul style="list-style-type: none"> FCC Class A CE RoHS